

Digital Multimeter

VICTOR®

85C

Technical data

Modle	85C		85D	
basic skills	Range	Precision	Range	Precision
DC voltage	2V/20V/200V	± (0.5%+3)	6V/60V	± (0.5%+3)
	600V	± (1.0%+10)	600V	± (1.0%+10)
AC voltage	2V	± (1.0%+5)	6V	± (0.8%+5)
	20V/200V	± (0.8%+5)	60V	
	600V	± (1.2%+10)	600V	± (1.2%+10)
DC current	600mA	± (1.0%+5)	600mA	± (1.0%+5)
	6A	± (1.5%+10)	6A	± (1.5%+10)
	10A	± (2.0%+5)	10A	± (2.0%+5)
AC current	600mA	± (1.5%+10)	600mA	± (1.5%+10)
	6A	± (2.0%+5)	6A	± (2.0%+5)
	10A	± (3.0%+10)	10A	± (3.0%+10)
Resistance	2000Ω	± (1.3%+5)	600Ω	± (1.3%+5)
	20kΩ/200kΩ	± (0.8%+3)	6kΩ/60kΩ/600kΩ	± (0.8%+3)
	2MΩ	± (1.5%+3)	6MΩ	± (1.5%+3)
	20MΩ	± (2.0%+10)	60MΩ	± (2.0%+10)
Capacitance	*		60nF/600nF/6uF/ 60uF/600uF	± (3.5%+20)
			6mF/60mF	± (5.0%+10)



TRUE RMS

Features	85C	85D
Display	LCD digital display	LCD digital display
Operation	Full intelligent automatic range	Full intelligent automatic range
Max display	1999	5999
Diode test	*	√
CAP	*	√
Firewire recognition	√	√
HOLD	√	√
NCV	√	√
Backlight	√	√
Overload	OL displayed on LCD	OL displayed on LCD
Low voltage	√	√
On-off beep	√	√
Operating°C	0~40°C <75%RH	0~40°C <75%RH
Store (°C)	-20~60°C <85%RH	-20~60°C <85%RH
Shut-down	√	√
Unit symbol	√	√
Resistance	10MΩ	10MΩ
Frequency response	40~1KHz	40~1KHz
Power supply	AAA 1.5V*2	AAA 1.5V*2
Product Size	146*72*50mm	146*72*50mm
Weight	210g	210g

85D



TRUE RMS

فروشگاه آذرپارتو

www.azarparto.com